

Sub-Floor and Flooring Attachment Index

Floor System	Mechanical Flooring Attachment	Mechanical Sub-Floor Attachment	Adhesive Sub-Floor Attachment
Aacer SuperBond Flex	Urethane Adhesive as recommended	Glue and use 1" Coated Staples 6" oc on the edge – 12" oc field	PL 400 or Equal
AacerChannel	2" Cleats	1" Coated Staples	NA
AacerChannel DIN	2" Cleats	1" Coated Staples	NA
AacerChannel VLP	1 ¾" Cleats	¾" Coated Staples	
AacerCush I	2" Cleats	NA	
AacerCush I Plus	2" Cleats	1" Coated Staples	
AacerCush II	2" Cleats	1" Coated Staples	
AacerFast	1 ¾" Cleats	NA	
Aacer FixedSleeper	2" Cleats	1" Coated Staples (A) 1 ½" Coated Staples (B)	
AacerFlex DIN	2" Cleats	1" Coated Staples	PL 400 or Equal
AacerFlex TP	2" Cleats	1" Coated Staples	PL 400 or Equal
AacerLoc	NA	NA	
Aacer SuperBond	Urethane Adhesive as recommended	1" Coated Staples	PL 400 or Equal
Anchored PowerSleeper DIN	1 ¾" Cleats	1" Coated Staples	
Anchored PowerSleeper Steel Encased	1 ¾" Cleats	1" Coated Staples	
PowerPlay DIN	2" Cleats	1" Coated Staples	
Power Play II	2" Cleats	1" Coated Staples	
PowerPlay LP	2" Cleats	1" Coated Staples	
PowerPlay VLP	2" Cleats	1" Coated Staples	
ScissorLoc	2" Cleats	1 ½" Coated Staples	
ScissorLoc DC	2" Cleats	1" Coated Staples	
ScissorLoc II	2" Cleats	1 ½" Coated Staples	
ScissorLoc III	2" Cleats	1 ½" Coated Staples	
ScissorLoc LP	2" Cleats	1" Coated Staples	
SuperAire II DC	2" Cleats	1" Coated Staples	
UltraChannel DC	2" Cleats	1" Coated Staples	
UltraFlex DC	2" Cleats	1 ½" Coated Staples	

- A. If ½" CDX Subfloor is called for
- B. If 1x6 or ¾" CDX is called for