

AcerShield MBX is a patented coated fiberglass reinforced membrane that suppresses moisture mitigation from the top surface of the concrete. AcerShield MBX has exceptional dimensional stability allowing it to lay flat.



1. Polymer Film Coating 2. Fiberglass Reinforced Membrane

Construction	4-ply Composite Product
Installation	Taped Using AcerShield Seam Tape
Roll Size	5' x 144' (720 sq. ft.)
Thickness	39.0 +/- 5.0 mils (ASTM D5729)
Basic Weight	11.5 - 13.5 lbs. / 100 sq. ft. (ASTM D2646)
Green Status and LEED Contributors	<ul style="list-style-type: none"> • Resource ReUse MRc3.1 & 3.2 • 100% Recyclable

BENEFITS

- Suppresses moisture emission levels in concrete - up to **99% RH** (ASTM F2170)
- Saves installation time & money
- Consistent performance
- Meets/exceeds typical property requirements of:
 - Acoustical ratings (ASTM E90-04); STC=52
 - Mold & Fungal Resistance (ASTM D3273) = No Growth
 - Fire & Flame Regulations
- 10 Year Limited Warranty
- Fast & easy to install - roll it out and tape it down. No mixing or special tools needed.
- Minimal prep work required
- Systems can be anchored through the barrier

It is the policy of Acer Flooring to continuously improve its line of products. Therefore, Acer Flooring reserves the right to change, modify or discontinue systems, specifications and accessories of all products at any time without notice or obligation to purchaser.



AacerShield is a patented coated fiberglass reinforced membrane that suppresses moisture mitigation from the top surface of the concrete. AacerShield has exceptional dimensional stability allowing it to lay flat.



1. Polymer Film Coating 2. Fiberglass Reinforced Membrane

Construction	4-ply Composite Product
Installation	Taped Using AacerShield Seam Tape
Roll Size	5' x 144' (720 sq. ft.)
Thickness	37.0 +/- 5.0 mils (ASTM D5729)
Basic Weight	11.5 - 13.5 lbs. / 100 sq. ft. (ASTM D2646)
Green Status and LEED Contributors	<ul style="list-style-type: none"> • Resource ReUse MRc3.1 & 3.2 • 100% Recyclable

BENEFITS

- Suppresses moisture emission levels in concrete - up to **95% RH** (ASTM F2170)
- Saves installation time & money
- Consistent performance
- Meets/exceeds typical property requirements of:
 - Acoustical ratings (ASTM E90-04); STC=52
 - Mold & Fungal Resistance (ASTM D3273) = No Growth
 - Fire & Flame Regulations
- 10 Year Limited Warranty
- Fast & easy to install - roll it out and tape it down. No mixing or special tools needed.
- Minimal prep work required
- Systems can be anchored through the barrier

It is the policy of Aacer Flooring to continuously improve its line of products. Therefore, Aacer Flooring reserves the right to change, modify or discontinue systems, specifications and accessories of all products at any time without notice or obligation to purchaser.

