

ScissorLoc III

Floor System Components



<p>Components Provided by Aacer Sports Flooring</p>	<p>Components Provided by Installer AVAILABLE FROM AACER *</p>
<p><u>Lower Subfloor</u> 1.6 LF Lineal Feet per SF</p> <p>1 x 6 (3/4 x 5-1/2") pine with resilient TriPower pads pre-attached. (Board lengths range from 6' to 12')</p> <div data-bbox="254 848 835 1276"> <p>2" SPACING OF UPPER AND LOWER SUBFLOOR</p> </div> <p><u>Upper Subfloor</u> 1.6 LF Lineal Feet per SF</p> <p>1 x 6 (3/4" x 5-1/2") pine. (Board lengths range from 6' to 16')</p> <p>NOTE: Quantities shown do not include waste.</p>	<p><u>Vapor Retarder</u> * 1 SF per SF</p> <p><u>1-1/2" Subfloor Staples</u> * 5.2 per SF</p> <p><u>2" Flooring Cleats or Staples</u> * 5.8 per SF</p> <ul style="list-style-type: none"> - When installing 2-1/4" Flooring - Fasteners applied 10" to 12" OC <p>OR</p> <p>8.7 per SF</p> <ul style="list-style-type: none"> - If installing 1-1/2" Flooring - Fasteners applied 10" to 12" OC <p><u>3/4" Solid Blocking</u></p> <p><u>Duct Tape</u> for Vapor Retarder</p>

REV A-24